

AlGaAs Infrared Laser Diode

ADL-78101TL

6-2D-LD78-003_Rev.03

★780nm 10mW 60 °C Reliable Operation!

• Features



1. Low operating current
2. High efficiency
3. Better power budget for optical design

• Applications

1. Industrial Tools

• Absolute maximum ratings

Parameter	Symbol	Condition	Rating	Unit
Light output power	P _O	CW	12	mW
Reverse voltage (LD)	V _{RL}	-	2	V
Reverse voltage (PD)	V _{RD}	-	30	V
Forward current (PD)	I _{FD}	-	10	mA
Case temperature	T _C	-	-10~+60	°C
Storage temperature	T _S	-	-40~+85	°C



• Electrical and optical characteristics (T_C=25 °C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Peak wavelength	λ	770	780	790	nm	P _o =10mW
Threshold current	I _{th}	-	15	25	mA	
Operating current	I _{op}	-	30	40	mA	P _o =10mW
Operating voltage	V _{op}	-	1.9	2.2	V	P _o =10mW
Differential efficiency	η	0.4	0.6	0.8	mW/mA	P _o =7-10mW
Monitor current	I _m	0.2	0.6	1.2	mA	P _o =10mW, V _{RD} =5V
Parallel divergence angle	$\theta_{ }$	7	11	15	deg	P _o =10mW
Perpendicular divergence angle	θ_{\perp}	24	28	32	deg	
Parallel FFP deviation angle	$\Delta\theta_{ }$	-2	0	+2	deg	
Perpendicular FFP deviation angle	$\Delta\theta_{\perp}$	-3	0	+3	deg	
Emission point accuracy	$\Delta x \Delta y \Delta z$	-80	0	+80	μ m	

• Precautions

- * Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- * Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- * Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- * Observing visible or invisible laser beams with the human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- * No laser device should be used in any application or situation where life or property is at risk in event of device failure.
- * Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.

* For reference only. Contents above are subject to change without notice.







Contact

For US, Canada Ayase America Inc. e-mail: info@ayaseamerica.com +1-408-988-5277
 For EU Ayase Europe GmbH e-mail: info@ayase-europe.de +49-0-6122-533-811
 For Japan Ayase Co., Ltd. e-mail: info@ayasecorporation.com +81-45-532-9501

AlGaAs Infrared Laser Diode

ADL-78101TL

6-2D-LD78-003_Rev.03



* For reference only. Contents above are subject to change without notice.

Contact

For US, Canada
For EU
For Japan

Ayase America Inc.
Ayase Europe GmbH
Ayase Co., Ltd.

e-mail: info@ayaseamerica.com
e-mail: info@ayase-europe.de
e-mail: info@ayasecorporation.com

+1-408-988-5277
+49-0-6122-533-811
+81-45-532-9501

